

SINGLE NEEDLE DOUBLE LOCKED STITCH MACHINE FOR EFFECTIVELY MANUFACTURING CONTAINER BAGS

SEWING PARTS WITH SPECIAL RUST PREVENTION COATING



80800CNH
with
Pedestal PN382A862L or
Pedestal PN382G132 or
Sewing Table UN382G132

- **STURDY**
- **EFFICIENT**
- **RELIABLE**
- **FAST**



SINGLE NEEDLE DOUBLE LOCKED STITCH MACHINE SEWING PARTS WITH RUST PREVENTION COATING

STITCH RANGE:	6.5 to 11 mm
STANDARD SETTING:	10 mm
SEWING CAPACITY:	up to 17 mm
STANDARD NEEDLE:	9848G 250/100
THREADS:	two, 2500 Denier (sewn off)
MAXIMUM SPEED:	1800 RPM (depending on sewing operation)
SEAM SPECIFICATION:	401 SSa-1

Machine Style	Description	Application	Threads for Needle and Loper	Required Installation
80800CNH	<p>Single needle double locked stitch machine <i>with special rust prevention coating.</i></p> <p>With built-in thread chain cutter and plain feed.</p> <p>Guide for filler cord from the top for sealing the needle punctures.</p> <p>Throat plate 80724C with guide for filler cord from below as an extra send and charge item.</p>	<p>For attaching filling and discharging tubes on CONTAINER BAGS.</p> <p>Crossing heavy seams is not possible.</p> <p>With electronic drives only: Stops adjustable in needle up and down position with simultaneously lifting the presser foot.</p>	<p>Polypropylene thread 1000 to 4000 Denier</p>	<p>PN382A862L Pedestal with clutchless electronic drive. Electro-pneumatic presser foot lifter.</p> <p>PN382G132 Pedestal with clutch motor (no automatic needle positioning). Mechanical presser foot lifter, foot treadle operated</p> <p>UN382G132 Sewing table with clutch motor (no automatic needle positioning). Mechanical presser foot lifter, foot treadle operated.</p>

Subject to change without notice © Union Special GmbH

Union Special LLC
One Union Special Plaza
Huntley, IL 60142, USA
Phone: 847/ 669 4500, Fax: 847/ 669 4239
www.unionspecial.com

Union Special GmbH
Raiffeisenstraße 3
71696 Möglingen / Germany
Tel: +49 (0)7141/247-0, Fax: +49 (0)7141/247-100
www.unionspecial-gmbh.com

03-19_en